



SOLIKAMSKBUMPROM

Technical Data Sheet SUPER LIGHT INTERLINER

The best interliner paper for cost-efficient corrugated board

100% fresh wood fibre

In harmony with nature

Parameter	Unit	Value			
		55	60	65	70
BASIC CHARACTERISTICS					
Basis weight (Grammage)	g/m ²	55.0±2.0	60.0±2.0	65.0±2.0	70.0±2.0
Moisture content	%	8.0±2.0			
STRUCTURAL CHARACTERISTICS					
Bulk	cm ³ /g	1.8-2.0			
Thickness	µm	100±4	110±4	115±4	125±4
OPTICAL CHARACTERISTICS					
Shade (CIE) brown	L	non- dimensional	70 ± 4.0		
	a		3.0±1.0		
	b		14.0±1.0		
Shade (CIE) yellow-brown	L	non- dimensional	70±4.0		
	a		4.0±1.0		
	b		22.0±1.0		
MECHANICAL CHARACTERISTICS					
Tensile Strength	machine direction	kN/m	min 2.7		
Bursting Strength		kPa	min 90		
OTHER CHARACTERISTICS					
Reel Diameter		mm	900-1250		
Reel Diameter Tolerance		mm	+20/-50		
Reel Width		mm	350-2500		
Reel Width Tolerance		mm	±2		
Mill Join Per Reel		piece	max 2		
Core		MM	76/100		
Wrapping			Strong Kraft Paper Strong Moisture proof polyethylene laminated Kraft paper		

Super lightweight paper 55-70 GSM
 Perfect paper with strong mechanical properties
 For medium layers of multilayer containerboard, converting and packaging
 100% biodegradable
 100% compostable
 100% recyclable

